



Enterprise HD IP Phone

—Standard Business IP Phone UC921P

UC921P delivers superior HD audio quality, rich and leading edge telephony features, all the functions of software are the same as other models. It is a perfect choice for small to medium businesses looking for a high quality, feature rich IP Phone at an affordable cost.

UC921P



IP PHONE THE FUTURE

www.htek.com



Phone Features

4 SIP accounts
Call hold, mute, DND
One-touch speed dial, hotline
Call forward, call waiting, call transfer
Redial, call return, auto answer, direct IP call
5-way conferencing
Group listening, SMS, emergency call
Ring tone selection/provisioning
Set date time automatically or manually
Dial plan for each account
RTCP-XR (RFC3611), VQ-RTCPXR (RFC6035)
Action URL/URI

Audio Features

HD Voice: HD Speaker, HD Handset
Codecs: iLBC, G.722, G.711(A/μ), Opus, G.723.1, G.729AB, G.726-32
DTMF: In-band, RFC 2833, SIP INFO
Full-duplex hands-free speakerphone with AEC
AEC, VAD, AGC, CNG, PLC, AJB

Directory

Local phonebook up to 1000 entries
XML/LDAP remote phonebook
Intelligent search method
Phonebook search/import/export
Call history: dialed/received/missed/forwarded
Black list

IP-PBX Features

Busy Lamp Field (BLF), bridged Line Appearance(BLA)
Anonymous call, anonymous call rejection
Hot-desking, voice mail
Call park, call pickup
Intercom, paging
Music on hold
Flexible seating
Call recording

Display and Indicator

2.8" 320x240-pixel color display with backlight
LED for call and message waiting indication
Dual-color(red or green) illuminated
LEDs for line status information
Wallpaper, multi-language selection
Intuitive user interface with icons and soft keys
Caller ID with name, number and photo

Feature keys

4 line keys with LED
4 line keys can be programmed up to 12 Paperless DSS keys (4-page view)
6 feature keys: voice mail, headset, mute, speaker, transfer, redial
4 context-sensitive soft keys
5 Navigation keys and volume control keys

Interface

Dual-port 10/100M Ethernet
Power over Ethernet (IEEE 802.3af), class 3
1xRJ9 (4P4C) handset port
1xRJ9 (4P4C) headset port

Physical Features

Stand with one angle at 40°
Wall mountable
External universal AC adapter :
AC 100~240V input and DC 5V/1.2A output
Power consumption (PSU): 1.8~4.4W
Power consumption (PoE): 2.3~5.3W
Operating humidity: 10~95%
Operating temperature: -10~50°C

Management

Configuration: browser/LCD-Menu/auto-provision
Auto provision via HTTP/HTTPS/FTP/TFTP
Auto-provision with PnP
Reset to factory, reboot
Local tracing log export, system log
Phone lock for personal privacy protection

Network and Security

SIP v1 (RFC2543), v2 (RFC3261)
SIP server/proxy redundancy
NAT Traversal: STUN mode
IP assignment: static/DHCP
HTTP/HTTPS web server
Time and date synchronization using SNTP
DNS-NAPTR/DNS-SRV(RFC 3263)
QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS DSCP
Transport Layer Security(TLS1.3), SRTP, ZRTP
HTTPS certificate manager
AES encryption for configuration file
Digest authentication using MD5/MD5-sess
IEEE802.1X/OpenVPN
IPv4/IPv6, LLDP/CDP/DHCP VLAN